



ACOUSTICS

PRECONFIGURED ACOUSTIC SOLUTIONS

Modular quiet zones for every work situation



FOR EFFECTIVE, PRECISE WORK RESULTS

Enhanced Concentration and Efficiency:

Effective sound insulation means improved concentration, precision, and efficiency in work environments with constant background noise. OTTOKIND's acoustic systems significantly reduce noise pollution, helping to prevent health risks and avoid costly production downtime. Our modular acoustic solutions can be tailored to any work situation, creating a comfortable and pleasant atmosphere for satisfied employees.



Effective noise
protection



Comfortable
working



Falling
costs



Modular
design


How our acoustic system works

Our acoustic panels consist of a sturdy sheet steel construction with both smooth and perforated sheet steel panels. Here's how they function:

Refraction: The perforated side of the panel refracts sound waves, dispersing them effectively.

Reflection: The smooth side reflects sound waves, preventing their transmission.

Insulation: There is a polyester fleece between the smooth and perforated sheet, which absorbs and insulates the sound.



ACOUSTIC PARTITION WALLS

Variable sound insulation with low space requirements

Acoustic partition wall systems “Quiet and waiting zones.”

Example configuration: U-shaped waiting area

- Width 2,232 mm x depth 1,138 mm x height 2,500 mm
- 5 x support incl., complete fastening material
- 4 x acoustic partitions, plug-in sheet metal modules, width 1,000 mm, depth 105 mm, height 2,500 mm
- One side perforated acoustic sheet, one side smooth sheet, absorber made of polyester fleece
- Paintwork RAL 7035 light grey



Acoustic partition wall systems “Small double workstations.”

Example configuration: Double workstation in T-shape

- Width 2,670 mm x depth 2,138 mm x height 2,500 mm
- 5 x support incl. complete fastening material
- 4 x acoustic partition walls, plug-in sheet metal modules, of which 2 x module width 1,250 mm and 2 x module width 1,000 mm, depth 105 mm, height 2,500 mm
- One side perforated acoustic sheet, one side smooth sheet, absorber made of polyester fleece
- Paintwork RAL 7035 light grey



Acoustic partition wall systems “Large double workstations”

Example configuration: Double workstation in double T-shape

- Width 2,670 mm x depth 2,232 mm x height 2,500 mm
- 7 x support incl. complete fastening material
- 6 x acoustic partition walls, plug-in sheet metal modules, of which 4 x module width 1,250 mm and 2 x module width 1,000 mm, depth 105 mm, height 2,500 mm
- One side perforated acoustic sheet, one side smooth sheet, absorber made of polyester fleece
- Paintwork RAL 7035 light grey

CLOSED ACOUSTIC CABINS

Quiet rooms in noisy environments

Office cubicles

Example configuration: Office cubicle with windows

- Width 4,230 mm x depth 3,230 mm x height 2,620 mm
- 14 x support incl., complete fixing material
- 13 x acoustic partition walls, plug-in sheet metal modules, width 1,000 mm, depth 105 mm, height 2,500 mm, including five window elements
- 4 x acoustic ceiling element with cross beams, width 1,000 mm, depth 3,000 mm
- One side perforated acoustic sheet, one side smooth sheet, absorber made of polyester fleece
- Paintwork outside RAL 7035 light grey, inside RAL 9010 pure white
- 3 x ceiling light
- 1 x door unit, width 1,000 mm, height 2,500 mm, lightweight honeycomb panel with excellent sound insulation



Telephone booths

Example configuration: "Mini" telephone booth

- Width 1,480 mm x depth 1,480 mm x height 2,620 mm
- 4 x support incl. complete fastening material
- 3 x acoustic partition walls, plug-in sheet metal modules, width 1,250 mm, depth 105 mm, height 2,500 mm
- 1 x acoustic ceiling element with cross beams, width 1,250 mm, depth 1,250 mm
- One side perforated acoustic sheet, one side smooth sheet, absorber made of polyester fleece
- Paintwork outside RAL 7035 light grey, inside RAL 9010 pure white
- 1 x ceiling light
- 1 x door unit, width 1,000 mm, height 2,500 mm, lightweight honeycomb panel with excellent sound insulation


OPEN ACOUSTIC BOOTHS

Islands of tranquillity with a wide range of applications


Acoustic booths with one open side

Example configuration: Open cabin

- Width 3,230 mm x depth 2,730 mm x height 2,620 mm
- 8 x support incl., complete fixing material
- 7 x acoustic partition walls, plug-in sheet metal modules, of which 3 x module width 1,000 mm and 4 x module width 1,250 mm, depth 105 mm, height 2,500 mm
- 2 x acoustic ceiling elements with cross beams, width 1,250 mm, depth 3,000 mm
- One side perforated acoustic sheet, one side smooth sheet, absorber made of polyester fleece
- Paintwork outside RAL 7035 light grey, inside RAL 9010 pure white
- 2 x ceiling light



Application example test laboratory



Meeting room application example



First Aid Point application example



MORE ACOUSTIC SOLUTIONS FOR INDIVIDUAL NEEDS

The OTTOKIND acoustic system has a modular structure. Our acoustic panels are available in three widths and three heights. They can be used to configure customised solutions and combined with windows, doors and other fittings. This results in modern sound insulation solutions perfectly tailored to the individual room. Talk to us!

OTTOKIND
ZUKUNFT EINRICHTEN

Otto Kind GmbH & Co. KG
Hagener Straße 35
51645 Gummersbach
Germany
Tel.: +49 2261 84 - 0
vertrieb@otto-kind.de
www.otto-kind.de

BAiBiAKIND
soluții complete pentru logistică și industrie

SC Baibia Kind SRL
Str. Poligonului nr. 9
100070 Ploiesti
Romania
Tel./Fax: +40 244 598 445
office@baibia.com
www.baibia.com

KIND
KIND FRANCE

Kind France S.A.R.L.
Garonor Est
Bâtiment 2b Cellule U
93600 Aulnay-sous-Bois
France
Tel.: +33 01 49 63 92 63
info@kind-france.fr
www.kind-france.com